

Fixit Quilt • Prints designed by Beth Logan, Quilt designed by Michele Wojcicki

Please read all instructions before starting. All measurements provided are approximate. Measure your quilt top before cutting.

Finished quilt measures approx. 45" x 63."

LEVEL: beginner

Yardage Requirements: *Yardage based on 42" fabrics.

- 1 Fixit Panel #2320-600
- 2 yards Border Stripe #2320-500
- 1/3 yard Nuts & Bolts #2320-306
- 1/8 yard Nuts & Bolts #2320-301
- 1/2 yard Hardwood #2320-209
- 5/8 yard Pegboard #2320-101

Cutting: LOF = Length of Fabric

From Fixit Panel #2320-600, cut:

Panel 24 x 42" for center

From Nuts & Bolt #2320-306, cut:

- 2 Strips 2 1/2" x 24" for first border
- 2 Strips 2 1/2" x 42" for first border

From Fixit Stripe #2320-500 cut:

- 2 Strips 4" x 34" LOF for third border. Fussy cut the stripe making sure the hammer, saw and saw blades are centered on the strip.
- 2 Strips 4" x 52" LOF for third border. Fussy cut the stripe making sure the hammer/saw and saw blades are centered on the strip.
- 2 Strips 2 1/2" x 64" LOF for outer border. Fussy cut the stripe making sure the nuts & bolts, hinges and pegboard are centered on the strip.
- 2 Strips 2 1/2" x 46" LOF for the outer border. Fussy cut the stripe making sure the nuts & bolts, hinges and pegboard are centered on the strip.

From Nuts & Bolts #2320-301 cut:

- 4 Squares 3 1/2" x 3 1/2" for second border cornerstones

From Hardwood #2320-209 cut:

- 2 Strips 3 1/2" x 28" for second border
- 2 Strips 3 1/2" x 46" for second border

From Pegboard #2320-101 cut:

- 4 Squares 2 1/2" x 2 1/2" for first border cornerstones
- 4 Squares 4" x 4" for third border cornerstones
- 6 Strips 2 1/2" for binding

Assembly: *Note: Set and press all seam allowances as directed. Use 1/4" seam allowance.

Piece the extra strip from cutting the 2 1/2" x 24" Nuts & Bolts strips to the remaining strips to make the 2 1/2" x 42" strips. Stitch them to the two sides of Panel. Press seams to the border. Piece the 2 1/2" Pegboard squares to each end of the 2 1/2" x 24" Nuts & Bolts strips. Press seams to the Nuts and Bolts strip. Stitch them to the top and bottom of the Panel. Press seams to the border.

Piece 3 Hardwood strips and cut to make 2 strips 3 1/2" x 46". Stitch them to the two sides of first border. Press seam to the Hardwood strips. Piece the dark Nuts & Bolts 3 1/2" squares to each end of the 3 1/2" x 28" Hardwood strips. Press seams to the Hardwood. Stitch them to the top and bottom of the first border. Press seams to the outside of the quilt.

Stitch the 4" x 52" fixit border print to the two sides of second border. Be sure to stitch the hammer/hand saw to the second border leaving the saw blades to the outside of the quilt. Press the seams to the hammers. Piece the 4" Pegboard squares to each end of the 4" x 34" Fixit border print strips. Press seams to the border stripe. Again be sure to stitch the hammer/hand saw side of the strip to the top and bottom second border. Press seams to the outside of the quilt.

Stitch the Nuts & Bolts, Hinges and Pegboard to the sides of the quilt. Find the center of each strip and the quilt top. Line up the centers and pin to the corners starting and stopping 1/4" from the corners. Be sure to stitch the Nuts & Bolts side of the strip to the quilt, leaving the Pegboard to the outside. After stitching the borders on miter the corners. Fold the quilt at the corner on point, lining up the borders. Mark a line from the corner at the end of stitching to the outside edge of the border strip at a 45 angle.

Layer and Quilt as desired.



